

Custodial Office

Silicone II Window & Door - Clear



MOMENTIVE
performance materials

Material Safety Data Sheet

Version: 1.10
10/05/2009

GE5000 12C-Crtrg (0.730 Lbs-0.331 Kg)
Silicone Rubber Sealant

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By: Waterford Plant
260 Hudson River Rd
Waterford NY 12188

Revised: 10/05/2009

Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use: Sealant
Formula: Mixture

HMIS

Flammability: 1 Reactivity: 0 Health: 1

NFPA

Flammability: 1 Reactivity: 0 Health: 1

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING! May be harmful if swallowed, inhaled or absorbed through skin. Irritating to eyes, respiratory system and skin. May cause central nervous system depression. May cause adverse reproductive effects.

Form: solid

Color: translucent

Odor: Ammonia

POTENTIAL HEALTH EFFECTS

INGESTION

May be harmful if swallowed. May cause central nervous system effects. May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

SKIN

Uncured product contact will irritate lips, gums and tongue. May cause skin irritation. May be absorbed through skin and produce effects as listed under "Ingestion".

INHALATION

Applies in uncured state. May cause respiratory tract irritation. May also cause other effects as listed under "Ingestion".

EYES

Eye irritation on contact with the uncured product.

MEDICAL CONDITIONS AGGRAVATED

Respiratory disorder Central nervous system disorders. Skin disorders.

SUBCHRONIC (TARGET ORGAN)

Liver; Central nervous system



MOMENTIVE
performance materials

Material Safety Data Sheet

Version: 1.10
10/05/2009

GE5000 12C-Crtrg (0.730 Lbs-0.331 Kg) Silicone Rubber Sealant

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

Dermal; Eyes

3. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION	CAS REG NO.	WGT. %
A. HAZARDOUS		
DISTILLATES (PETROLEUM),	64742-46-7	1 - 5 %
HYDROTREATED MIDDLE		
Hexamethyldisilazane	999-97-3	1 - 5 %
Methyltrimethoxysilane	1185-55-3	1 - 5 %
B. NON-HAZARDOUS		
Treated Filler	68611-44-9	10 - 30 %
Polydimethylsiloxane	63148-62-9	10 - 30 %
Methoxypolydimethylsiloxane	68037-58-1	60 - 100 %

4. FIRST AID MEASURES

INGESTION

Do not induce vomiting. If victim is conscious, give 1-3 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention if irritation persists.

SKIN

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water. If skin irritation persists, call a physician.

INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get



MOMENTIVE
performance materials

Material Safety Data Sheet

Version: 1.10
10/05/2009

GE5000 12C-Crtrg (0.730 Lbs-0.331 Kg) Silicone Rubber Sealant

medical attention if irritation persists.

NOTE TO PHYSICIAN

Treatment is symptomatic and supportive.

5. FIRE-FIGHTING MEASURES

FLASH POINT:	> 93.3 °C; 200 °F
METHOD:	estimated
FLAMMABLE LIMITS IN AIR - LOWER (%):	no data available
FLAMMABLE LIMITS IN AIR - UPPER (%):	no data available

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Avoid contact with skin and eyes. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation. Product releases methanol during application and curing.

STORAGE

Store away from heat, sources of ignition, and incompatibles. Keep out of the reach of children. Keep container tightly closed.



MOMENTIVE
performance materials

Material Safety Data Sheet

Version: 1.10
10/05/2009

GE5000 12C-Crtrg (0.730 Lbs-0.331 Kg) Silicone Rubber Sealant

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

Showers; Eyewash stations; Exhaust ventilation

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

PROTECTIVE GLOVES

Rubber or plastics gloves

EYE AND FACE PROTECTION

Safety glasses with side-shields

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

Component	CAS RN	Source	Value
-----------	--------	--------	-------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F:	no data available
FREEZING POINT:	no data available
PHYSICAL STATE:	solid
ODOR:	Ammonia
COLOR:	translucent
pH:	no data available
SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):	Soluble in toluene
VOLATILE ORGANIC CONTENT:	2.2 %(m)
VOC EXCL. H2O & EXEMPTS (G/L):	27 g/l



MOMENTIVE
performance materials

Material Safety Data Sheet

Version: 1.10
10/05/2009

GE5000 12C-Crtrg (0.730 Lbs-0.331 Kg)

Silicone Rubber Sealant

10. STABILITY AND REACTIVITY

STABILITY

Stable

HAZARDOUS POLYMERIZATION

Will not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide (CO₂); Carbon monoxide; Silicon dioxide.; Methanol; formaldehyde; This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL

Remarks: no data available

ACUTE DERMAL

Remarks: no data available

ACUTE INHALATION

Remarks: no data available

OTHER

Contains dibutyltin compound(s) - May impair fertility. May cause harm to unborn child.

SENSITIZATION

no data available

SKIN IRRITATION

no data available

EYE IRRITATION

no data available



MOMENTIVE
performance materials

Material Safety Data Sheet

Version: 1.10
10/05/2009

GE5000 12C-Crtrg (0.730 Lbs-0.331 Kg) Silicone Rubber Sealant

MUTAGENICITY

no data available

OTHER EFFECTS OF OVEREXPOSURE

Methanol released during curing.

12. ECOLOGICAL INFORMATION

ECOTOXICITY

Ecotoxicological data for this product is not available.

DISTRIBUTION

no data available

CHEMICAL FATE

no data available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

Further Information:

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION

Inventories

Canada DSL Inventory	y (positive listing)
Korea Existing Chemicals Inventory (KECI)	y (positive listing)
China Inventory of Existing Chemical Substances	y (positive listing)
Australia Inventory of Chemical Substances (AICS)	y (positive listing)
Philippines Inventory of Chemicals and Chemical	y (positive listing)



MOMENTIVE
performance materials

Material Safety Data Sheet

Version: 1.10
10/05/2009

GE5000 12C-Crtrg (0.730 Lbs-0.331 Kg) Silicone Rubber Sealant

Substances (PICCS)

EU list of existing chemical substances y (positive listing)

Canada NDSL Inventory n (Negative listing)

Japan Inventory of Existing & New Chemical Substances n (Negative listing)

(ENCS)

TSCA list y (positive listing)

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

US Regulatory Information

SARA (311,312) HAZARD CLASS

Acute Health Hazard; Chronic Health Hazard

SARA (313) CHEMICALS

58-36-6, 10, 10'-oxybisphenoxarsine.

CALIFORNIA PROPOSITION 65

WARNING! This product contains a chemical known in the State of California to cause cancer.
108-88-3, Toluene.

Canadian Regulatory Information

WHMIS HAZARD CLASS

D2B - Toxic Material Causing Other Toxic Effects

Other

SCHDLE B/HTSUS: 3214.10.00.10 Mastic based on rubber

ECCN: EAR99

16. OTHER INFORMATION

OTHER

C = ceiling limit NEGL = negligible EST = estimated NF = none found NA = not applicable
UNKN = unknown NE = none established REC = recommended ND = none determined
V = recommended by vendor SKN = skin TS = trade secret R = recommended
MST = mist NT = not tested STEL = short term exposure limit ppm = parts per million
ppb = parts per billion By-product = reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2)., These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.



MOMENTIVE
performance materials

Material Safety Data Sheet

Version: 1.10
10/05/2009

GE5000 12C-Crtrg (0.730 Lbs-0.331 Kg)
Silicone Rubber Sealant
