

MATERIAL SAFETY

PRODUCT TRADE NAME:

HOMAX PRODUCTS, INC.

OOPS! ALL PURPOSE REMOVER ITEM #710744,710729,710755,710756,710757 710802,710833,710834,710855,710754

| HAZARDOUS MATERIAL INFORMATION SYSTEM | |
|--|---|
| HEALTH | 3 |
| FLAMMABILITY | 3 |
| REACTIVITY | 0 |
| PROTECTIVE EQUIPMENT | В |

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: HOMAX PRODUCTS, INC.

468 WEST HORTON ROAD 3ELLINGHAM, WA 98226

24 HOUR EMERGENCY PHONE NUMBER:

CHEMTREC

1-800-424-9300

INFORMATION PHONE NUMBER:

1-800-729-9029

DATE OF PREPARATION:

09/16/03

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

<7%

%

COMPONENT MONOCHLOROTOLUENE

(MIXED ISOMERS)

ETHYL ALCOHOL XYLENE (MIXED ISOMERS) VM& P NAPTHA

<12% NONE

>21% 1330-20-7 >58% 64742-89-8

CAS#

95-49-8

TLV (UN ITS) 50PPM

1000PPM

100PPM

300 PPM

OSHA PEL 50PPM

1000PPM 100PPM 300 PPM

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

APPEARANCE AND ODOR:

BOILING POINT:

THIN COLORED LIQUID/SOLVENT SWEET PERFUME ODOR. 173 (REPRESENTS LOWEST BOILING OF INDIVIDUAL RAW MATERIALS)

<1 (ETHER =1)

EVAPORATION RATE: VAPOR PRESSURE(MMHG/70F)

N/A

WATER SOLUBILITY (%):

INSOLUBLE

VAPOR DENSITY: (AIR = 1) SPECIFIC GRAVITY (WATER = 1)

6.627 POUNDS PER GALLON

MELTING POINT:

>1

SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT:

50 F TAG CLOSED CUP

FLAMMABLE LIMITS:

N/A

EXTINGUISHING MEDIA:

WATER FOG, FOAM, DRY CHEMICAL, CARBON DIOXIDE

LEL: N/A UEL: N/A

SPECIAL FIRE FIGHTING PROCEDURES: DO NOT USE DIRECT STREAM OF WATER ON POOL FIRES.

PRODUCT WILL FLOAT AND CAN BE REIGNITED FROM WATER.

PROTECTIVE EQUIPMENT:

APPROVED SELF-CONTAINED BREATHING APPARATUS & FULL

BUNKER GEAR SHOULD BE WORN.

UNUSUAL FIRE & EXPLOSION HAZARDS:

KEEP CONTAINERS COOL WITH WATER. PRESSURE BUILD UP

COULD RESULT IN CONTAINER RUPTURE. MATERIAL IS HEAVIER

THAN AIR.

SECTION V - REACTIVITY DATA

STABILITY:

STABLE

INCOMPATIBILITY (MATERIALS TO AVOID):

CHLORINATED COMPOUNDS AND OXIDIZIING MATERIALS.

CONDITIONS TO AVOID:

HEAT, HOT SURFACES AND ALL SOURCES OF IGNITION.

HAZARDOUS DECOMPOSITION PRODUCTS:

CHLORINE GAS, HCL AND OTHER CHLORINATED COMPOUNDS, CARBON DIOXIDE, CARBON MONOXIDE, UNIDENTIFIED ORGANICS MAY BE FORMED DURING COMBUSTION.

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

CONDITIONS TO AVOID (POLY):

NONE.

SECTION VI - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

INHALATION: RUNNY NOSE, SORE THROAT, COUGHING, CHEST DISCOMFORT, SHORTNESS OF BREATH AND REDUCED LUNG FUNTION.

INGESTION: SORE THROAT, ABDOMINAL PAIN, NAUSEA, VOMITING AND DIARRHEA.

EYES: IRRITATION INCLUDING PAIN, TEARING, REDDENING AND SWELLING.

SKIN: REDDENING, SWELLING, RASH AND REDNESS.

CHRONIC: MAY CAUSE INJURY TO KIDNEYS AND LIVER. LOSS OF MEMORY, INTELLECTUAL AND COORDINATION ABILITY. IN EXTREME CASES, UNCONSCIOUSNESS AND DEATH MAY OCCUR.

CARCINOGENICITY: NONE LISTED NTP, IARC OR OSHA.

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: REMOVE TO AREA FREE FROM VAPORS AND SUPPORT/RESTORE BREATHING. SEEK MEDICAL ATTENTION IMMEDIATELY.

INGESTION: DO NOT INDUCE VOMITING!!! IF VOMITING SPONTANEOUSLY OCCURS, KEEP VICTIM'S HEAD BELOW HIPS TO PREVENT ASPIRATION INTO LUNGS. SEEK MEDICAL ATTENTION IMMEDIATELY.

EYES: FLUSH WITH WATER FOR 15 MINUTES. SEEK MEDICAL ATTENTION IMMEDIATELY.

SKIN: REMOVE CONTAMINATED CLOTHING AND WASH AFFECTED AREA WITH SOAP AND WATER. DO NOT REUSE CONTAMINATED ARTICLES. SEEK MEDICAL ATTENTION IMMEDIATELY.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS IF MATERIAL IS RELEASED OR SPILLED:

FOR LARGE SPILLS, EVACUATE THE HAZARD AREA OF UNPROTECTED PERSONNEL. WEAR APPROPRIATE RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF SOURCES OF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN. IF VAPOR CLOUD FORMS, WATER FOG MAY BE USED TO SUPRESS. CONTAIN RUN-OFF. REMOVE VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ABSORBANT SUCH AS CLAY, SAND OR OTHER SUITABLE MATERIAL. PLACE IN NON-LEAKING CONTAINERS. SEAL TIGHTLY FOR PROPER DISPOSAL.

NEUTRALIZING AGENTS: N/A

WASTE DISPOSAL METHOD: DO NOT FLUSH INTO SEWERS OR WATERWAYS. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS-HANDLING/STORING: KEEP PRODUCT CONTAINERS COOL, DRY AND AWAY FROM SOURCES OF IGNITION. USE AND STORE WITH ADEQUATE VENTILIATION IN PROPERLY LABELED, CLOSED CONTAINERS. AVOID INHALATION OF VAPORS AND SKIN CONTACT. DO NOT TAKE INTERNALLY!! DISPOSAL CONTAINERS MUST BE SEALED TIGHTLY AND PROPERLY LABELED. DO NOT EAT, DRINK OR SMOKE IN WORK AREA. WASH HANDS THOROUGHLY AFTER USE.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: IF EXOSURE EXCEEDS TLV, USE NIOSH APPROVED RESPIRATOR.

VENTILATION: USE EXPLOSION PROOF VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS.

PROTECTIVE GLOVES; CHEMICAL RESISTANT

EYE PROTECTION: SPLASHPROOF GOGGLES

OTHER PROTECTIVE CLOTHING & EQUIPMENT: SAFETY SHOWERS AND EYE WASH STATIONS SHOULD BE

AVAILABLE FOR USE IN AN EMERGENCY.

WORK HYGENIC PRACTICES: WASH HAND THOROUGHLY AFTER USE, BEFORE DRINKING, EATING OR SMOKING. SUPPLIER SAFETY & HEALTH DATA: N/A

SECTION XI - DISCLAIMER

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HERE IN IS ACCURATE, OBTAINED FROM SOURCES BELIEVED BY HOMAX CORPORATION TO BE ACCURATE. SINCE THE CONDITIONS AND METHODS OF USE OF OUR PRODUCTS ARE BEYOND OUR CONTROL, WE DESCLAIM ANY AND ALL LIABILITY ARISING OUT OF THE IMPROPER USE OF THESE PRODUCTS OR THE INFORMATION PROVIDED HEREWITH.

SHIPPING INFORMATION:

HAZARD CLASS: ORM-D

DOT SHIPPING NAME: CONSUMER COMMODITY

UN NUMBER: N/A

NA #: N/A

OTHER: THE ORM-D CLASSIFICATION APPLIES TO CONTAINERS UNDER ONE GALLON IN SIZE AND IS NOT APPLICABLE TO AIR SHIPMENT.