

3M General Offices 3M Center St. Paul, MN 55144-1000 1-800-364-3577 or (651) 737-6501 (24 hours)

5/13/2011 10:13:23 AM

## **Material Safety Data Sheet**

Purchase Order #: Customer Number: 298418 STZ1043

& SERVICES
HILLYARD ROSE PRODUCTS
545 STIMMEL RD
COLUMBUS, OH 43223-2901
United States of America

### Dear & SERVICES

Enclosed is the Material Safety Data Sheet (MSDS) for the product that your company recently purchased from 3M

Please forward the attached MSDS to the individual in your organization responsible for implementing these regulations.

If you are a distributor and resell this product, OSHA and EPA require that you transmit this MSDS information to your customers at the time of first shipment or whenever you receive revised MSDSs from 3M.

3M MSDSs are available over the Internet at www.3m.com/MSDSSearch. You may also order a CD-ROM of 3M MSDSs by calling 1-800-364-3577.

3M is committed to meeting our customer requirements. Please contact your 3M customer service or sales representative if you have any questions. If you do not know whom to contact, please call the 3M Product Information Center at 1-800-364-3577.

If you are not currently receiving 3M MSDSs by e-mail and would like to do so, please contact our eMSDS Administrator at emsdsadmin@mmm.com or by calling 651-736-5875.



### **Material Safety Data Sheet**

Copyright, 2011, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3MTM TroubleShooterTM Baseboard Stripper

MANUFACTURER:

DIVISION:

Building & Commercial Services Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000

### EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 04/21/11

Supercedes Date: 07/06/09

Document Group: 10-2818-2

#### Product Use:

Intended Use:

Baseboard Stripper

Specific Use:

Heavy duty aerosol cleaner removes soil, grease and finish buildup. Upside down spray

feature for hard-to-reach places. Use on baseboards, floor edges, corners, stairways and

ceramic tile. Contains no ozone depleting chemicals.

### **SECTION 2: INGREDIENTS**

Ingredient WATER 2-BUTOXYETHANOL PETROLEUM GASES, LIQUEFIED, SWEETENED ETHANOLAMINE NON-IONIC SURFACTANT PEDRIMAES	C.A.S. No. 7732-18-5 111-76-2 68476-86-8 141-43-5 68131-39-5 Mixture	% by Wt 60 - 90 10 - 30 5 - 10 3 - 7 0.1 - 1.0 0.1 - 1.0
PERFUMES D-LIMONENE	Mixture 5989-27-5	0,1 - 1,0 0.0558

### SECTION 3: HAZARDS IDENTIFICATION

### 3.1 EMERGENCY OVERVIEW

Specific Physical Form: Aerosol

Odor, Color, Grade: Off white, milky liquid.

General Physical Form: Liquid

### MATERIAL SAFETY DATA SHEET 3MTM TroubleShooterTM Baseboard Stripper 04/21/11

Immediate health, physical, and environmental hazards: Aerosol container contains flammable gas under pressure. May cause severe eye irritation. May cause target organ effects.

### 3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

May be absorbed through skin and cause target organ effects.

Inhalation

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Initation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

### SECTION 4: FIRST AID MEASURES

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

### 4.2 NOTE TO PHYSICIANS

## MATERIAL SAFETY DATA SHEET 3MTM TroubleShooterTM Baseboard Stripper

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

## SECTION 5: FIRE FIGHTING MEASURES

### 5.1 FLAMMABLE PROPERTIES

Autoignition temperature Flash Point Flammable Limits(LEL) Flammable Limits(UEL) OSHA Flammability Classification: No Data Available Not Applicable No Data Available No Data Available Not Applicable

### 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

### 5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Unusual Fire and Explosion Hazards: Not applicable. Closed containers exposed to heat from fire may build pressure and explode. Aerosol container contains flammable material under pressure.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Observe precautions from other sections. Ventilate the area. WARNING | A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. If it can be done safely, place the leaking container in an exhaust hood or well- ventilated area. Contain spilled material. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Cover, but do not seal for 48 hours.

6.2. Environmental precautions

Place depressurized can and clean up wastes in a closed container approved for transportation by appropriate authorities. Dilute in a large excess of water. Carefully, and with stirring, add appropriate dilute acid such as sulfamic acid or vinegar. Confirm neutrality. Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Clean-up methods

Contain spilled material. Clean up residue. Place depressurized can and clean up wastes in a closed container approved for transportation by appropriate authorities. Contain spill. For large spills, if necessary, get assistance from professional spill clean up team. For small spills, carefully neutralize spill by adding appropriate dilute acid such as vinegar. Work slowly to avoid boiling or spattering. Continue to add neutralizing agent until reaction stops. Let cool before collecting. Or use a commercially available caustic (alkaline or basic) spill clean-up kit. Follow kit directions exactly. Collect as much of the spilled material as possible. Clean up residue with detergent and water.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

## SECTION 7: HANDLING AND STORAGE

### MATERIAL SAFETY DATA SHEET 3MTM TroubleShooter M Baseboard Stripper 04/21/11

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Do not pierce or burn container, even after use. No smoking while handling this material. Do not spray near flames or sources of ignition. Avoid breathing of vapors, mists or spray. Aerosol container contains flammable gas under pressure. Avoid eye contact with vapors, mists, or spray. Keep out of the reach of children. Avoid contact with oxidizing agents. Avoid skin contact.

Store away from acids. Store away from heat. Store out of direct sunlight. Do not store containers on their sides. Store away from oxidizing agents.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 ENGINEERING CONTROLS

Use in a well-ventilated area. Do not use in a confined area or areas with little or no air movement.

## 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

### 8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Safety Glasses with side shields

Indirect Vented Goggles

### 8.2.2 Skin Protection

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Butyl Rubber

Neoprene

Nitrile Rubber.

Avoid breathing of vapors, mists or spray. Under normal use conditions, airborne exposures are not expected to be significant enough 8.2.3 Respiratory Protection to require respiratory protection.

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

## 8.3 EXPOSURE GUIDELINES

8.3 EXPOSURE GUIDELER	•	_	<u>Limit</u>	Additional Information
Ingredient 2-BUTOXYETHANOL 2-BUTOXYETHANOL D-LIMONENE ETHANOLAMINE ETHANOLAMINE	Authority ACGIH OSHA AIHA ACGIH ACGIH OSHA	Tyde TWA TWA TWA TWA STEL TWA	20 ppm 240 mg/m3 165.5 mg/m3 3 ppm 6 ppm 6 mg/m3	Skin Notation*
ETHANOLAMINE		11 Avenorure h	v the cutaneous rot	ite including mucous membr

<sup>\*</sup> Substance(s) refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

## SOURCE OF EXPOSURE LIMIT DATA:

### MATERIAL SAFETY DATA SHEET 3MTM TroubleShooter Baseboard Stripper 04/21/11

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:

Odor, Color, Grade:

General Physical Form:

Autoignition temperature

Flash Point

Flammable Limits(LEL)

Flammable Limits(UEL)

Boiling Point

Density

Vapor Density

Vapor Pressure

Specific Gravity

pΗ

Melting point

Solubility in Water

**Evaporation rate** 

Volatile Organic Compounds

Kow - Oct/Water partition coef

Percent volatile

**VOC Less H2O & Exempt Solvents** 

Viscosity

Aerosol

Off white, milky liquid.

Liquid

No Data Available

Not Applicable

No Data Available

No Data Available

Approximately 212 ºF

Approximately 1

No Data Available

No Data Available

Approximately 1 [Ref Std: WATER=1]

11 - 12

Not Applicable

Complete

No Data Available

10 - 49 % [Test Method: calculated per CARB title 2]

No Data Available

78 - 100 %

345 - 1050 g/l [Test Method: calculated per CARB title 2]

No Data Available

## SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

Heat

Sparks and/or flames

10.2 Materials to avoid

Strong oxidizing agents

Strong acids

Hazardous Polymerization: Hazardous polymerization will not occur.

### Hazardous Decomposition or By-Products

Substance
Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition
Not Specified
Not Specified
Not Specified

MATERIAL SAFETY DATA SHEET 3MTM TroubleShooter M Baseboard Stripper 04/21/11

Oxides of Nitrogen

Not Specified

## SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

### SECTION 12: ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

A 3M Product Environmental Data Sheet (PED) is available.

### CHEMICAL FATE INFORMATION

A 3M Product Environmental Data Sheet (PED) is available.

## SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste. Facility must be capable of handling aerosol cans. Dispose of empty product containers in a sanitary landfill,

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14:TRANSPORT INFORMATION

ID Number

UPC

ID Number

UPC

61-5000-6131-4

00-48011-14001-8

FZ-0100-0465-8

FZ-0100-0466-6

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: REGULATORY INFORMATION

### US FEDERAL REGULATIONS

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient 2-BUTOXYETHANOL (GLYCOL ETHERS) C.A.S. No 111-76-2

STATE REGULATIONS

**CHEMICAL INVENTORIES** 

The components of this product are in compliance with the chemical notification requirements of TSCA.

### MATERIAL SAFETY DATA SHEET 3MIM TroubleShooterIM Baseboard Stripper 04/21/11

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS. The components of this material are in compliance with the new chemical notification requirements for the Korean Existing Chemicals Inventory.

The components of this product are listed on the Australian Inventory of Chemical Substances.

All the components of this product are listed on China's Inventory of Chemical Substances.

The components of this product are in compliance with notification requirements in the Philippines.

The components of this product are listed on the Canadian Domestic Substances List.

### INTERNATIONAL REGULATIONS

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 Flammability: 2 Reactivity: 0 Special Hazards: None Aerosol Storage Code: 1

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 Flammability: 2 Reactivity: 0 Protection: X - See PPB section.

Hazardous Material Identification System (HMIS®) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint and Coatings Association (NPCA).

Revision Changes:

Section 1: Product name was modified.

Section 16: Disclaimer (second paragraph) was modified.

Section 8: Eye/face protection information was modified.

Section 8: Skin protection - recommended gloves information was modified.

Section 14: Transportation legal text was modified.

Page Heading: Product name was modified.

Section 15: Inventories information was modified.

Section 9: Boiling point information was modified.

Section 5: Flammable limits (UE) information was modified.

Section 5: Flammable limits (LEL) information was modified.

Section 9: Property description for optional properties was modified.

Section 9: Flammable limits (LEL) information was modified.

Section 9: Flammable limits (UEL) information was modified.

Section 8: Exposure guidelines ingredient information was modified.

Section 6: 6.2. Environmental precautions heading was added.

Section 6: 6.1. Personal precautions, protective equipment and emergency procedures heading was added.

## MATERIAL SAFETY DATA SHEET 3M131 TroubleShooter M Baseboard Stripper 04/21/11

Section 10.1 Conditions to avoid heading was added.

Section 10.2 Materials to avoid heading was added.

Section 16: Web address was added.

Section 6: Personal precautions information was added.

Section 6: Environmental procedures information was added.

Section 6: Methods for cleaning up information was added.

Section 10: Materials to avoid physical property was added.

Section 10: Conditions to avoid physical property was added.

Section 1: Address was added.

Copyright was added.

Company logo was added.

Section 6: Clean-up methods heading was added.

Telephone header was added.

Company Telephone was added.

Section 1: Emergency phone information was added.

Section 1: Emergency phone information was deleted.

Company Logo was deleted.

Copyright was deleted.

Section 16: Web address heading was deleted.

Section 6: Release measures information was deleted.

Section 6: Release measures heading was deleted.

Section 10: Materials and conditions to avoid physical property was deleted.

Section 1: Address line I was deleted.

Section 1: Address line 2 was deleted.

Section 8: Exposure guidelines legend was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com

·			
		,	-
			AND DE SECTION OF THE
			**************************************