#### **3M General Offices**

3M Center St. Paul, Minnesota 55144-1000 (612) 733-1110

Duns No.: 00-617-3082

MATERIAL SAFETY DATA SHEET



DIVISION: Building Service & Cleaning Products TRADE NAME: 3M Brand Carpet Protector Concentrate 3M I.D. NUMBER: 61-5000-0262-3

ISSUED: MAY 16, 1988 SUPERSEDES: AUGUST 26, 1987 DOCUMENT: 10-2825-7

1. INGREDIENT	C.A.S. NO.	PERCENT	VALUE UNIT	LIMITS TYPE AUT
Water 2-Butoxyethanol Isopropyl alcohol 1,1,2-trichloro-1,2,2-	7732-18-5 111-76-2 67-63-0 76-13-1	62.0 - 72.0 17.0 - 19.0 3.0 - 5.0 0.0 - 1.0	NONE NONE 25 ppm 400 ppm 1000 ppm	NONE NON TWA ACG TWA ACG TWA ACG
trifluoroethane Fluoroaliphatic acid salt (non- hazardous)	NONE	5.0 - 8.0	NONE NONE	NONE NON
Surfactants (non-hazardous)	NONE	0.0 - 2.0	NONE NONE	ноне нон

#### SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- NONE: None Established

## 2. PHYSICAL DATA

BOILING POINT:.... 190.00 F N/D VAPOR PRESSURE:..... VAPOR DENSITY: ..... N/D EVAPORATION RATE:.... N/D SOLUBILITY IN WATER: ..... complete pH: .....VISCOSITY: ..... APPEARANCE AND ODOR: Clear, liquid, mild odor

# 3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: ... 130.00 F T.C.C. FLASH POINT:.....FLAMMABLE LIMITS - LEL: .....
FLAMMABLE LIMITS - UEL: .... N/D N/D

AUTOIGNITION TEMPERATURE: ... N/D

**EXTINGUISHING MEDIA:** 

dry chemical.

Carbon dioxide, foam, dry chemi SPECIAL FIRE FIGHTING PROCEDURES: N/A

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NFPA-HAZARD-CODES: HEALTH 1 UNUSUAL REACTION HAZARD: NONE FIRE 2 REACTIVITY 0

#### 4. REACTIVITY DATA

STABILITY: Stable INCOMPATIBILITY - MATERIALS TO AVOID: Protect from freezing. Store above 50 F (49 C). **3M General Offices** 

3M Center St. Paul, Minnesota 55144-1000 (612) 733-1110

Duns No.: 00-617-3082

MATERIAL SAFETY DATA SHEET

BW

MSDS: 3M Brand Carpet Protector Concentrate MAY 16, 1988

PAGE: 2 of 3

#### 4. REACTIVITY DATA

### (continued)

HAZARDOUS POLYMERIZATION: Will Not Occur HAZARDOUS DECOMPOSITION PRODUCTS: CO, carbon dioxide

#### 5. ENVIRONMENTAL INFORMATION

#### SPILL RESPONSE:

Observe precautions from other sections. Extinguish all ignition sources. Cover with absorbent material. Collect spilled material. Place in a U.S. Dept. of Transportation approved metal container, and seal. Clean up residue with water.

#### RECOMMENDED DISPOSAL:

Discharge spent treatment solutions and small product quantities (< 5 gal.) into wastewater treatment system. Disposal alternative, incinerate after mixing with flammable material in a permitted hazardous waste facility. Empty container may be sanitary landfilled. Since regulations vary, consult applicable regulations or authorities before disposal.

## **ENVIRONMENTAL DATA:**

Chemical Oxygen Demand (COD): 0.53 g/g. 5-Day Biochemical Oxygen Demand (BOD5): 0.32 g/g. 14-Day Biochemical Demand (BOD20): 0.39 g/g. 96-Hour LC50, Fathead minnow (Pimephales promelas): between 500 ml and 1000 ml/l.

SCAQMD Rule 443 and 443.1 - Non-photochemically reactive solvent; VOC - 245 g/l; VOC (less water and exempt) = 225 g/l.

#### 6. SUGGESTED FIRST AID

#### EYE CONTACT:

Immediately flush eyes with plenty of water. Continue for 10 minutes holding eyelids open. Call a physician.

### SKIN CONTACT:

Wash affected area with soap and water.

### INHALATION:

Remove person to fresh air.

#### IF SWALLOWED:

Call a physician.

#### OTHER FIRST AID:

NONE

## 7. PRECAUTIONARY INFORMATION

Keep product away from heat, sparks and flames. Use only in areas adequately ventilated with enough air movement to remove vapors and prevent vapor build up. Prevent eye contact. Avoid prolonged breathing of vapors and prolonged or repeated skin contact. Keep

#### **3M General Offices**

3M Center St. Paul, Minnesota 55144-1000 (612) 733-1110

Duns No.: 00-617-3082

MATERIAL SAFETY DATA SHEET

3M

MSDS: 3M Brand Carpet Protector Concentrate MAY 16, 1988

PAGE: 3 of 3

## 7. PRECAUTIONARY INFORMATION (continued)

container closed when not in use. Keep out of reach of children.

### ADDITIONAL EXPOSURE LIMITS

	EXPOSURE		LIMITS	
INGREDIENTS	VALUE	UNIT	TYPE	
2-Butoxyethanol	120	mg/m3	· TWA	ACGIH
2-Butoxyethanol	50	ppm_	TWA	OSHA
2-Butoxyethanol	240	mg/m3	TWA	OSHA
Isopropyl alcohol	980	mg/m3	TWA.	ACGIH
Isopropyl alcohol	500	ppm_	STEL	ACGIH
Isopropyl alcohol	1225	mg/m3		ACGIH
Isopropyl alcohol	400	ppm_	TWA	OSHA
Isopropyl alcohol	980	mg/m3	TWA	OSHA
1,1,2-trichloro-1,2,2-	7600	mg/m3	TWA	ACGIH
trifluoroethane				
1,1,2-trichloro-1,2,2-	1250	ppm	STEL	ACGIH
trifluoroethane				
1,1,2-trichloro-1,2,2-	9500	mg/m3	STEL	ACGIH
trifluoroethane				
1,1,2-trichloro-1,2,2-	1000	ppm	TWA	OSHA
trifluoroethane				
1,1,2-trichloro-1,2,2-	7600	mg/m3	TWA	OSHA
trifluoroethane				

## SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- OSHA: Occupational Safety and Health Administration

### 8. HEALTH HAZARD DATA

EYE CONTACT: Liquid concentrate was moderately irritating to the eyes of laboratory animals. Direct contact may produce corneal opacity. The diluted concentrate did not show corneal opacity.

SKIN CONTACT: Liquid concentrate was found to be non-irritating and non-sensitizing to the skin of laboratory animals. 2-Butoxyethanol may be absorbed through the skin and may cause blood changes based on animal studies.

INHALATION: Acute inhalation studies conducted with laboratory animals indicated the spray to be non-toxic via inhalation.

INGESTION: Liquid concentrate was found to be slightly to moderately toxic to laboratory animals. The diluted concentrate was found to be practically non-toxic orally. 2-Butoxyethanol may cause blood changes based on animal studies.

Abbreviations: N/D - Not Determined N/A - Not Applicable

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this Data Sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user.