

66

13-629 THRU 13-647

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form OSHA 200
OMB No. 44-101307

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1918, 1917)

SECTION I

MANUFACTURER'S NAME Dennison Manufacturing Co., Dennison Carter's Division		EMERGENCY TELEPHONE NO. (617) 879-0511 X4636
ADDRESS (Number, Street, City, State, and ZIP Code) 300 Howard St., Bldg. 26-2, Framingham, MA 01701		
CHEMICAL NAME AND SYNONYMS N.A.		TRADE NAME AND SYNONYMS Carter's Stamp Pad Inks
CHEMICAL FAMILY N.A.	FORMULA N.A.	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS	-		BASE METAL		
CATALYST	-		ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
Although none of the ingredients are classified as hazardous materials by OSHA terms, Ethylene Glycol has an LD ₅₀ of 6,000 mg/kg.					

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	212°F	SPECIFIC GRAVITY (H ₂ O=1)	1.08
VAPOR PRESSURE (mm Hg.)	0.1	PERCENT. VOLATILE BY VOLUME (%)	None
VAPOR DENSITY (AIR=1)	N.A.	EVAPORATION RATE (_____ = 1)	1.0
SOLUBILITY IN WATER	Complete		
APPEARANCE AND ODOR	Dark liquid, mild odor		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	240°F	FLAMMABLE LIMITS	Lel	Uel
EXTINGUISHING MEDIA	N.A.			
SPECIAL FIRE FIGHTING PROCEDURES	N.A.			
UNUSUAL FIRE AND EXPLOSION HAZARDS	N.A.			

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE
 Non-Toxic per CFR 1500.3 (C)(2)(1). LD50 is greater than 5.0 g/kg of body wt.
 EFFECTS OF OVEREXPOSURE
 Is not considered a primary irritant. Black and Red: non eye irritant. Blue,
 purple, brown and green are considered to be eye irritants. -CFR 1500.42.
 EMERGENCY AND FIRST AID PROCEDURES
 Eye contact: Blue, purple, brown and green- Flush with plenty of water. Call a
 physician. Skin contact: Wash with soap and water.

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (Materials to avoid)			
HAZARDOUS DECOMPOSITION PRODUCTS			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Flush with water. Absorb with towels or cloth.

WASTE DISPOSAL METHOD

Flush with water. Adhere to state and local regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)

N.A.

VENTILATION	LOCAL EXHAUST.	SPECIAL
	N.A.	
	MECHANICAL (General)	
	N.A.	OTHER

PROTECTIVE GLOVES
 Not necessary

EYE PROTECTION
 If desired

OTHER PROTECTIVE EQUIPMENT
 None

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Normal

OTHER PRECAUTIONS

Because Blue, purple, brown and green stamp pad inks could be irritating to the eyes, it would be good practice to keep out of the reach of small children.