

S.C. Johnson Wax
Racine, Wisconsin 53403-5011
Phone: (414) 631-2777
Emergency Phone: (800) 228-5635

4=Very High
3=High
2=Moderate
1=Slight
0=Insignificant

HAZARD RATING	
HMIS	NFPA
1 Health	
2 Flammability	
0 Reactivity	

MATERIAL SAFETY DATA SHEET

SECTION I-PRODUCT IDENTIFICATION

PRODUCT NAME: RUGBEE SOLVENT SPOTTER			PRODUCT CODE 13860-2	
CHEMICAL OR COMMON NAME NA	DATE ISSUED: 09/03/91	SUPERSEDES: 06/29/90	PREPARED BY: Terry A. Meyers Chemical Info. Adm.	

SECTION II-INGREDIENT INFORMATION

INGREDIENTS	WEIGHT %	EXPOSURE LIMIT
Mineral Spirits (CAS# 64741-41-9)	65-75	1000ppm (ACGIH TLV-TWA); 500ppm (OSHA PEL)
[SARA, PA, NJ, MA] Glycol Ether (CAS# 34590-94-8)	20-30	100ppm (ACGIH TLV-TWA); 100 ppm (OSHA PEL)
Alkoxylated Linear Alcohols (CAS#)	2-8	NE
[SARA, PA, NJ, MA] Xylene (CAS# 1330-20-7)	2-4	100ppm (ACGIH TLV-TWA); 100ppm (OSHA PEL)
See Regulatory Information (Section XII) for explanation of bracketed information.		

SECTION III-PHYSICAL DATA

APPEARANCE/ODOR: Clear, light liquid with citrus and solvent odor.	SPECIFIC GRAVITY (H2O=1): ND
VAPOR PRESSURE (mm Hg): ND	PERCENT VOLATILE BY VOLUME (%): NA
SOLUBILITY IN WATER: Negligible	VAPOR DENSITY (Air=1): ND
FREEZING POINT (3F): ND	BOILING POINT (3F): ND
pH: ND	EVAPORATION RATE (Butyl Acetate=1): ND
VOC (as packaged, minus H2O):	THEORETICAL VOC (lb/gal):

SECTION IV-FIRE AND EXPLOSION INFORMATION

FLASH POINT (3F) (Method Used): 105 (TCC)
FLAMMABLE LIMITS: NA
EXTINGUISHING MEDIA: Foam. CO2. Dry Chemical. Water Fog.
SPECIAL FIREFIGHTING PROCEDURES: Fire fighters should wear self-contained breathing apparatus and protective clothing.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Container may burn and leak in heat of fire.

MATERIAL SAFETY DATA SHEET

S.C. Johnson Max
1525 Howe Street
Racine, Wisconsin 53403

RUGBEE SOLVENT SPOTTER
Product Number: 13860
Serial Number: 2

Page 2

SECTION V-HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY: Ingestion.

SIGNS AND SYMPTOMS: Direct contact of product with eyes can cause irritation. Prolonged or repeated contact of product with skin may cause irritation. If taken internally, aspiration of liquid product can cause chemical pneumonitis.

FIRST AID PROCEDURES: Flush eyes with water for 15 minutes. If irritation persists, seek medical aid. Wash skin with plenty of water. If irritation persists, seek medical aid. If product is swallowed, do not induce vomiting. Seek medical aid at once.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE:

SECTION VI-REACTIVITY DATA

STABILITY: Stable

STABILITY-CONDITIONS TO AVOID: None known

INCOMPATIBILITY: None known

HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to fire, produces normal products of combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID: None known

SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb with oil-dri or similar inert material. Eliminate all ignition sources. Wear/use appropriate protective equipment.

WASTE DISPOSAL INFORMATION: Disposal of regulated quantities should be by incineration at a permitted facility in accordance with all Federal/State regulations and local ordinances regarding disposal of ignitable wastes.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: If mists/vapors are not adequately controlled by local ventilation, use appropriate respiratory protection to prevent overexposures.

VENTILATION: General room ventilation is normally adequate. Substantial amounts of mists/vapors can be controlled with local exhaust ventilation or respiratory protection.

PROTECTIVE GLOVES: If prolonged or repeated contact is possible: Any impervious material.

FIRE PROTECTION: No special requirements under normal use conditions.

OTHER PROTECTIVE MEASURES: Use good personal hygiene practices.

SECTION IX-SPECIAL PRECAUTIONS

REGULATORY LABELING: DANGER: Contains synthetic surfactants, petroleum distillates and glycol ethers. Do not mist product as inhalation may cause respiratory damage. COMBUSTIBLE. Do not use near open flame. Harmful or fatal if swallowed.

MATERIAL SAFETY DATA SHEET

S.C. Johnson Max
1525 Howe Street
Racine, Wisconsin 53403

RUGBEE SOLVENT SPOTTER
Product Number: 13860
Serial Number: 2

Page 3

SECTION IX-SPECIAL PRECAUTIONS (cont.)

OTHER HANDLING AND STORAGE CONDITIONS: Store in a cool, dry place with adequate ventilation. Wash thoroughly after handling. Keep from freezing. Keep out of reach of children.

SECTION X-ADDITIONAL INFORMATION

ADDITIONAL INFORMATION: NA

SECTION XI-TRANSPORTATION INFORMATION

DOT CLASS: 15 14

DOT #: NA

SHIPPING NAME: Cleaning, scouring or washing compounds. NOI. Liquid.

DOT NOTES: None

SECTION XII-REGULATORY INFORMATION

There are no ingredients subject to the reporting requirements under California's Proposition 65.

MA - These ingredients are subject to the reporting requirements under the Massachusetts Hazardous Substance List.

NJ - These ingredients are subject to the reporting requirements under the New Jersey Right to Know Hazardous Substance List.

PA - These ingredients are subject to the reporting requirements under the Pennsylvania Hazardous Substance List.

SARA - These ingredients are subject to the reporting requirements under the Superfund Amendments and Reauthorization Act of 1986 Title III, Section 313 and 40 CFR Part 372.

NA-Not Applicable, ME-Not Established, MSR-Not Special Requirement, MD-Not Determined

The information herein is given in good faith. No warranty expressed or implied is made. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and local laws and regulations. The information contained in this form is confidential and is submitted solely for your organization's internal use.